

型號	FDM-2	FDM-5	FDM-12	FDM-20
冷凝器溫度	啟動後10分鐘內可降至-50/-84°C以下(室溫20°C)			
最低真空度	幫浦啟動後10分鐘內可降至40mTorr以下			
水凍結量	2 L	5 L	12 L	20 L
歧管數	8	12	16	24
熱氣融冰	Option	Yes	Yes	Yes
電壓	110/220V	220V	220V	220V
尺寸W×D×H	46×50×56cm	50×60×78cm	82×75×80cm	82×75×80cm

歧管式冷凍乾燥機

Manifold Freeze Dryer



冷凍乾燥瓶				
Flask Size	Complete Flask	Flask Bottom	Flask Top	Filter
150ml	1010150	1000150	1012000	1012001
300ml	1010300	1000300	1012000	1012001
600ml	1010600	1000600	1011000	1011001
1200ml	1011200	1001200	1011000	1011001

真空幫浦			
Catalog Number	Description		Oil Mist
1050205	RV5 , Pumping speed 103 L/min , Ultimate total pressure $2*10^{-3}$ mbar		1065005
1050136	GLD-N136 , Pumping speed 165 L/min , Ultimate pressure $6.7*10^{-3}$ mbar		1065012
1050212	RV12 , Pumping speed 283 L/min , Ultimate total pressure $2*10^{-3}$ mbar		1065012

Catalog Number	Description
1051001	1L高真空幫浦油
1051004	4L高真空幫浦油
1080001	手動封瓶裝置
1030001	推車(FDM-2)
	IQ/OQ Document



智慧型全自動控制
觸控式彩色螢幕